

## TECHNICAL DATA

# CARRIER SYSTEM SYSTEM 2000

## 1200 x 1000 mm

## PRODUCT BENEFITS

- Non-slip transportation of all common EPP, KLT and Euro-stacking box systems
- No stretching or tying required
- Replacement for steel flat pallets and Euro wooden pallets – the clean and light alternative

### TECHNICAL DATA

Basic dimensions:	1,200 x 1,000 mm
Tare:	29 kg
Payload (max.):	350 kg
High rack (without base):	no

### CAPACITY UTILISATION IN MEGA-TRAILER (13.6 x 2.48 x 3.0 m)

Storage positions: 26

1	2	3	4	5	6	7	8	9	10	11	12	13
14	15	16	17	18	19	20	21	22	23	24	25	26



	PALLET	LID	OPTIONS*
Material	PE	PE	<ul style="list-style-type: none"> <li>• Additional lashing systems, as 2-fold or 4-fold elements for small stackable containers (VDA) and foam containers (EPP/EPE).</li> <li>• Coloured markings, individual lettering</li> </ul>
Grammage	–	–	
Equipment	Open surface, 9 feet 4-way entry pallet Drainage holes	2 handles, red	



### Safety

Additional lashing systems\* (optionally) make sure that everything remains firmly in place. They are available as 2-fold or 4-fold elements.



### Stability

The raised pallet edge prevents the load carriers from slipping. This ensures optimum stacking.



### Marking

All pallets can be identified by coloured markings\* (optionally) and individual lettering.