

TECHNICAL DATA

CARRIER SYSTEM SYSTEM 2000

1200 x 800 mm

PRODUCT BENEFITS

- Non-slip transportation of all common EPP, KLT and Euro-stacking box systems
- No stretching or tying required
- Replacement for steel flat pallets and Euro wooden pallets – the clean and light alternative

TECHNICAL DATA

Basic dimensions: 1,200 x 800 mm

Tare: 25 kg

Payload (max.): 350 kg

High rack (without base): no

CAPACITY UTILISATION IN MEGA-TRAILER (13.6 x 2.48 x 3.0 m)

Storage positions: 32

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32



	PALLET	LID	OPTIONS*
Material	PE	PE	<ul style="list-style-type: none"> • Additional lashing systems, as 2-fold or 4-fold elements for small stackable containers (VDA) and foam containers (EPP/EPE). • Coloured markings, individual lettering
Grammage	–	–	
Equipment	Open surface, 9 feet 4-way entry pallet Drainage holes	2 handles, red	



Safety

Additional lashing systems* (optionally) make sure that everything remains firmly in place. They are available as 2-fold or 4-fold elements.



Stability

The raised pallet edge prevents the load carriers from slipping. This ensures optimum stacking.



Marking

All pallets can be identified by coloured markings* (optionally) and individual lettering.