TECHNICAL DATA

SYSTEM 2000 SEA CONTAINER SMALL

1130 x 725 x 730 mm

PRODUCT BENEFITS

- Perfect for shipping with sea container
- Robust, durable three-piece container
- Low container weight
- Non-slip sandwich folding
- Intuitive, fast, ergonomic handling
- Protection against water and dirt



Hang-in lid

- Saving of space at the place of use
- Extra ergonomics and easy handling

Visual inspection of empties

• Direct check of the completeness of all elements (sleeve contained in empties)






Scan for more information.





Secure empty unit

- Protection of the folded sleeve
- No damage to the containers by slipping
- Safe and stable stacking



Integrated base insert*

- No loss of base insert, as firmly attached to the sleeve
- Fixation of sleeve with pallet in assembled, loaded condition



Safe stacking

- No tying necessary
- Fast, safe and uncomplicated stacking of the full and empty containers



^{*}Container with integrated base insert, optionally available for System 2000.

TECHNICAL DATA

SYSTEM 2000 SEA CONTAINER SMALL

1130 x 725 x 730 mm



TECHNICAL DATA

External dimensions: 1,130 x 725 x 730 mm
Internal dimensions: 1,060 x 660 x 560 mm
Volume: 392 l
Tare weight: 26 kg
Empties height: 200 mm in a stack
Folding system: Sandwich folding

High rack (without base):

LOADS

Payload (max.): 200 kg
Stacking load (max.): 900 kg
Stacking factor: 1+4
(with max. payload and stacking load)

LOGISTICS AND TRANSPORT

Return rate (Mega-Trailer): 1:3.5


Volume reduction (Mega-Trailer): 71%

Return rate (40 ft high cube): 1:4

Volume reduction (40 ft high cube): 75%

CAPACITY UTILISATION IN MEGA-TRAILER (13.6 x 2.48 x 3.0 m)

Full/Empty: 144/504




Storage positions: 36

no

1	2	3	4	5	6	7	8	9	10	11	12
13	14	15	16	17	18	19	20	21	22	23	24
25	26	27	28	29	30	31	32	33	34	35	36

CAPACITY UTILISATION IN 40FT HIGH CUBE (13.6 x 2.48 x 3.0 m)

Full/Empty: 90/360



Storage positions 30

1	2	3	4	5	6	7	8	9	10
11	12	13	14	15	16	17	18	19	20
21	22	23	24	25	26	27	28	29	30









SANDWICH	PALLET	SLEEVE	LID		
Material	PE	PP	PE		
Grammage	-	3000 g/m ²	-		
Equipment* *optional; further options available	Open surface, 6 feet 4-way entry pallet Drainage holes	M-folding 2 label holders A5 Integrated base insert *	2 handles, black Suspension lugs Control opening		

You can get on request further options like a higher or lower sleeve, additional flap doors, individual printing, tracking systems as well as customized inside packaging solutions - just contact us.







