TECHNICAL DATA

SYSTEM 2000 FLIPTOP

1500 x 1200 x 990 mm

PRODUCT BENEFITS

- Robust, durable three-piece container
- Low container weight
- Non-slip sandwich folding
- Intuitive, fast, ergonomic handling
- Protection against water and dirt
- No manual locking required



Hinged lid

- Saving of space at the place of use
- Extra ergonomics and easy handling

Visual inspection of empties

• Direct check of the completeness of all elements (sleeve contained in empties)





Scan for more information.





Secure empty unit

- Protection of the folded sleeve
- No damage to the containers by slipping
- Safe and stable stacking



Integrated base insert*

- No loss of base insert, as firmly attached to the sleeve
- Fixation of sleeve with pallet in assembled, loaded condition



Safe stacking

- No tying necessary
- Fast, safe and uncomplicated stacking of the full and empty containers



TECHNICAL DATA

SYSTEM 2000 FLIPTOP

1500 x 1200 x 990 mm



TECHNICAL DATA

External dimensions: $1,500 \times 1,200 \times 990 \text{ mm}$ **Internal dimensions:** $1,430 \times 1,130 \times 799 \text{ mm}$

Volume: 1,291 l

Tare weight:49 kgEmpties height:227 mm in a stackFolding system:Sandwich folding

High rack (without base):

LOADS

Payload (max.):250 kgStacking load (max.):1,250 kgStacking factor:1+4

(with max. payload and stacking load)

LOGISTICS AND TRANSPORT

Return rate: 1:4.3 Volume reduction: 77 %


CAPACITY UTILISATION IN MEGA-TRAILER (13.6 x 2.48 x 3.0 m)

Full: 54



Empty: 234

0 VOLUME-



Storage positions: 18

1	2	3	4	5	6	7	8	9
10	11	12	13	14	15	16	17	18









SANDWICH	PALLET	SLEEVE	LID
Material	PE	PP	PE
Grammage	-	3000 g/m ²	-
Equipment* further options available	Open surface, 9 feet 4-way entry pallet Drainage holes	M-folding 1 flap door 800 x 350 mm 2 label holders A5 Integrated base insert *	6 handles, black Hinged

You can get on request further options like additional flap doors, individual printing, tracking systems as well as customized inside packaging solutions – just contact us.

