TECHNICAL DATA

SYSTEM 2000-H SMARTFIX®

1800 x 1200 x 990 mm

PRODUCT BENEFITS

- Super-fast folding technique
- Extremely easy handling
- Sliding lid
- Firmly connected components
- High payloads possible
- Protection against water and dirt



Easy handling

• The handle strap on front of the lid allows one-handed operation

Firm connection

- Lid, sleeve and pallet form a firmly connected unit
- Lid stop for hanging the lid







Secure empty unit

- Protection of the folded sleeve
- No damage to the containers by slipping
- Safe and stable stacking



Scan for more information.



Integrated base insert*

- No loss of base insert, as firmly attached to the sleeve
- Fixation of sleeve with pallet in assembled, loaded condition



Safe stacking

- No tying necessary
- Fast, safe and uncomplicated stacking of the full and empty containers



TECHNICAL DATA

SYSTEM 2000-H SMARTFIX®

1800 x 1200 x 990 mm



TECHNICAL DATA

External dimensions: 1,800 x 1,200 x 990 mm **Internal dimensions:** 1,735 x 1,135 x 794 mm

Volume: 15641
Tare weight: 66 kg

Empties height: 215 mm in a stack **Folding system:** Sandwich folding

High rack (without base):

LOADS

Payload (max.):350 kgStacking load (max.):1,250 kgStacking factor:1+3

(with max. payload and stacking load)

LOGISTICS AND TRANSPORT

Return rate: 1:4.3 Volume reduction: 77%


CAPACITY UTILISATION IN MEGA-TRAILER (13.6 x 2.48 x 3.0 m)

Full: 42



Empty: 182

77% VOLUME-



Storage positions: 14

1	2	3	4	5	6	7
8	9	10	11	12	13	14









SANDWICH	PALLET	SLEEVE	LID
Material	PE	PP	PE
Grammage	-	3000 g/m ²	-
Equipment* further options available	Open surface, 8 feet 4-way entry pallet Steel reinforced Drainage holes	M-folding 1 flap door 800 x 350 mm 2 label holders A5 Integrated base insert *	2 handles, black2 handles, blue1 handle strap, blue

You can get on request further options like additional flap doors, individual printing, tracking systems as well as customized inside packaging solutions – just contact us.







