TECHNICAL DATA

SYSTEM SUPERQUAD SMARTFIX®

1230 x 830 x 980 mm

PRODUCT BENEFITS

- SuperQuad as wire mesh replacement
- Extremely stable pallet design
- High payloads possible
- Super-fast folding technique
- Extremely easy handling
- Firmly connected components



Safe guidance

 Embedded guide rails simplify handling – the lid is neatly guided when opening and closing

Firm connection

 Lid and sleeve form a firmly connected unit – no more individual parts, no more loss of container parts



Closed pallet deck

- No soiling
- No base insert required



Automatic locking

- No extra handles necessary
- Engage principle for firm fixation



- Protection of the folded sleeve
- No damage to the containers by slipping
- Safe and stable stacking



Packaging Solutions

TECHNICAL DATA

SYSTEM SUPERQUAD **SMARTFIX®**

1230 x 830 x 980 mm



TECHNICAL DATA

External dimensions: 1,230 x 830 x 980 mm **Internal dimensions:** 1,195 x 795 x 780 mm Volume: 741 l Tare weight: 45 kg

Empties height: 220 mm in a stack Folding system: Sandwich folding yes

High rack (without base):

LOADS

Payload (max.): 500 kg Stacking load (max.): 1,250 kg **Stacking factor:** 1+2

(with max. payload and stacking load)

LOGISTICS AND TRANSPORT


Return rate: 1:4.3 Volume reduction: 77%

CAPACITY UTILISATION IN MEGA-TRAILER (13.6 x 2.48 x 3.0 m)

Full: 96



Empty: 416



Storage positions: 32

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32









SANDWICH	PALLET	SLEEVE	LID
Material	PE	PP	PE
Grammage	-	3000 g/m ²	-
Equipment further options available	Closed surface, 4 feet 4-way entry pallet Steel reinforced Drainage holes 4 brackets for ring	M-folding 1 flap door 800 x 350 mm 2 label holders A5 4 latching trough (for pallet) 2 latching holes (for lid)	2 handles, black1 handle, blaueSuspension lugs2 brackets (for sleeve)

You can get on request further options like a individual printing or tracking systems for example.







