TECHNICAL DATA

SYSTEM SUPERQUAD

1230 x 830 x 980 mm

PRODUCT BENEFITS

- SuperQuad as wire mesh replacement
- Extremely stable pallet design
- High payloads possible
- Intuitive, fast and ergonomic handling
- Protection against water and dirt
- No manual locking required



Hang-in lid

- Saving of space at the place
- Extra ergonomics and easy handling

Secure empty unit

- Protection of the folded sleeve
- No damage to the containers by slipping
- Safe and stable stacking







Scan for more information.



Robust pallet foot

- Firm, one-piece connection of foot and pallet
- High level of stability suitable for high rack and roller conveyor
- Drainage holes



Closed pallet deck

- No soiling
- No base insert required

Automatic locking

- No extra handles necessary
- Engage principle for firm fixation



TECHNICAL DATA

SYSTEM SUPERQUAD

1230 x 830 x 980 mm



TECHNICAL DATA

External dimensions: 1,230 x 830 x 980 mm
Internal dimensions: 1,195 x 795 x 780 mm
Volume: 741 l
Tare weight: 44 kg

Tare weight:44 kgEmpties height:220 mm in a stackFolding system:Sandwich folding

High rack (without base):

LOADS

Payload (max.): 500 kg Stacking load (max.): 1,250 kg Stacking factor: 1+2


(with max. payload and stacking load)

LOGISTICS AND TRANSPORT

Return rate: 1:4.3 **Volume reduction:** 77%

CAPACITY UTILISATION IN MEGA-TRAILER (13.6 x 2.48 x 3.0 m)


Full: 96



Empty: 416

yes

00 VOLUME-REDUCED



Storage positions: 32

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32









SANDWICH	PALLET	SLEEVE	LID
Material	PE	PP	PE
Grammage	-	3000 g/m ²	-
Equipment further options available	Closed surface, 4 feet 4-way entry pallet Steel reinforced Drainage holes 4 brackets for ring	M-folding 1 flap door 800 x 350 mm 2 label holders A5 4 latching trough (for pallet) 2 latching holes (for lid)	2 handles, blackSuspension lugs2 brackets (for sleeve)

You can get on request further options like a individual printing or tracking systems for example.







